







Sensor chip and photoelectric conversion apparatus using the same

Patent number: EP0382540
Publication date: 1990-08-16
Inventor: NAKAMURA KENICHI KOTOBUKIHAITS; KOIDE YOSHIO CANON DAINI HONAT
Applicant: CANON KK (JP)
Classification:
- **International:** G11C19/00; H04N1/18; H04N3/15
- **European:** G11C19/00; H04N1/193; H04N1/193B; H04N3/15G; H04N3/15J
Application number: EP19900301355 19900208
Priority number(s): JP19890030015 19890210; JP19890030016 19890210; JP19890030018 19890210

Also published as:

 EP0382540 (A3)
 EP0382540 (B1)

Cited documents:

 EP0260956
 GB2160058
 EP0292253
 JP61214564

[Report a data error here](#)

Abstract of EP0382540

A sensor chip includes output signal lines for outputting signals outside the sensor chip from light-receiving elements of the sensor chip, a switch for connecting/disconnecting the output signal lines, and a controller for closing the switch only for a duration including a time interval in which signals are output outside the sensor chip from the light-receiving elements, and opening the switch for a duration except for the duration. A multichip photoelectric conversion apparatus in which a plurality of sensor chips each having a plurality of light-receiving elements are arranged, includes output signal lines, connected to a common signal line, for outputting signals outside the sensor chip from light-receiving elements of the sensor chip, a switch, provided for each of the sensor chips, for connecting/disconnecting the output signal lines, and a controller, provided in each of the sensor chips, for closing the switch only for a duration including a time interval in which signals are output outside the sensor chip from the light-receiving elements, and opening the switch for a duration except for the duration.

